

# Long Length Hose

## Air

### ***DAAS A/S Air Hose***

300 psi anti-static air hose

Anti-static in accordance with BS ISO 2878 (supersedes BS 2050)

Meets or exceeds the performance requirements of BS5118/2 & BS EN ISO 2398/2B L-T



**Cover:** Black synthetic rubber, ozone and weather resistant.  
Anti static rubber compounds.

**Branding:** Antistatic Air BS ISO 2878 20 Bar - size (mm)  
Antistatic Air BS 2050 20 Bar - size (mm) month  
& year of manufacture (embossed on rear)

**Reinforcement:** High tensile synthetic textile plies.

**Tube:** Black synthetic rubber.

**Resistance:**  $<1 \times 10^6 \Omega/\text{metre}$

**Temperature:** From -20°C to +100°C

**Safety Factor:** 3:1 Minimum

| I.D | O.D | W.P | B.P. | Weight |
|-----|-----|-----|------|--------|
| mm  | mm  | Bar | Bar  | kg/m   |
| 6   | 14  | 20  | 64   | 0.210  |
| 10  | 19  | 20  | 64   | 0.350  |
| 13  | 21  | 20  | 64   | 0.370  |
| 19  | 29  | 20  | 64   | 0.640  |
| 25  | 36  | 20  | 64   | 0.900  |