

EOLO CLIP 400°C

Special coated glass fabric duct reinforced with a stainless steel wire

Applications

Where it is necessary a flame retardant hose for suction of smokes, vapours, welding gasses, furnace exhaust, dust and fibres.

Technical Features

special coated glass fabric duct reinforced with a stainless steel wire. Galvanized steel clamp profile.

Properties

Highly flexible and robust, very high temperature resistant up to 400°C, extremely compressible ca. 3:1, really good in bending, external steel helix protects against abrasion, flame retardant according to DIN 4102-B1

Temperature range

-60°C +400°C / -76°F +752°F

Technical data						
Part number	Inside ø (mm)	Outside ø (mm)	Weight (g/m)	Vacuum (mH2O)	Bending radius (mm)	Coil length (m)
H4 01 050	50	62,0	740	3,80	19	6
H4 01 055	55	67,0	800	3,50	21	6
H4 01 060	60	72,0	870	3,20	22	6
H4 01 065	65	77,0	940	2,90	24	6
H4 01 070	70	82,0	1000	2,60	25	6
H4 01 075	75	87,0	1070	2,30	27	6
H4 01 080	80	92,0	1130	2,00	28	6
H4 01 090	90	102,0	1260	1,40	31	6
H4 01 100	100	112,0	1000	1,20	45	6
H4 01 110	110	122,0	1090	1,05	49	6
H4 01 120	120	132,0	1190	0,90	53	6
H4 01 125	125	137,0	1230	0,85	55	6
H4 01 130	130	142,0	1280	0,75	57	6
H4 01 140	140	152,0	1380	0,60	61	6
H4 01 150	150	162,0	1000	0,50	32	6
H4 01 160	160	172,0	1070	0,45	34	6
H4 01 175	175	187,0	1160	0,40	38	6
H4 01 180	180	192,0	1200	0,40	38	6
H4 01 200	200	212,0	1320	0,30	42	6
H4 01 215	215	227,0	1420	0,30	46	6
H4 01 225	225	237,0	1480	0,25	48	6
H4 01 250	250	262,0	1650	0,25	52	6
H4 01 275	275	287,0	1810	0,20	58	6
H4 01 300	300	312,0	1970	0,15	62	6
H4 01 350	350	362,0	2290	0,15	72	6
H4 01 400	400	412,0	2610	0,10	82	6
H4 01 450	450	462,0	2930	0,10	92	6
H4 01 500	500	512,0	3250	0,05	102	6
H4 01 600	600	612,0	3890	0,04	122	3
H4 01 700	700	712,0	4540	0,02	142	3
H4 01 800	800	812,0	5180	0,02	162	3
H4 01 900	900	912,0	5820	0,01	182	3

