

NEODUCT

Flexible ducting made of one ply of neoprene coated glass

Applications

Exhaust Gas, Industrial ventilation, Automotive, and Plastic Industries.

Technical Features

Single ply neoprene coated glass fabric ducting, internally reinforced with steel wire helix. External glass cord.

Properties

The product is lightweight, highly flexible, kink proof, very good in bending, nearly smooth inside, good resistance to most chemicals and high temperature up to 130°C (peak 150°C), halogens free. Standard Length - 4m.

Temperature range

-55°C +130°C (peak 150°C) / -67°F +266°F (peak 302°F)

Technical data						
Part number	Inside ø (mm)	Weight (g/m)	Vacuum (mH2O)	Working pressure (bar)	Bending radius (mm)	Coil length (m)
P801025	25	120	5,3	1,4	12	4
P801032	32	130	5	1,4	16	4
P801038	38	165	5	1,4	19	4
P801041	41	177	4,5	1,3	21	4
P801051	51	250	4,4	1,2	25	4
P801063	63	300	4	1,1	31	4
P801070	70	395	3,5	1,1	35	4
P801083	83	470	3	1,0	41	4
P801089	89	495	2,9	0,9	44	4
P801102	102	570	2,6	0,9	51	4
P801121	121	760	1,9	0,8	60	4
P801127	127	805	1,7	0,8	63	4
P801152	152	1050	1,4	0,6	76	4
P801160	160	1090	1,4	0,6	80	4
P801178	178	1210	1,2	0,6	89	4
P801203	203	1380	0,7	0,5	101	4
P801254	254	1650	0,5	0,4	127	4
P801305	305	2000	0,3	0,1	152	4

Other sizes are available on request

