

T276

ANTIFIRE H0N

Dorngefertigter Haspelschlauch für Wasser und flüßige Löschmittel, geeignet für Feuerwehrtankwagen. Starke und flexible Ausführung. Gemäß **BS3169/1986 A2**

Mandrel built hose for water and liquid fire extinguishing mediums. Suitable for reels on trucks for fire brigades. Strong and flexible structure. Complies with **BS3169/1986 A2**



Technische Daten

Seele	Schwarzes EPDM Gummi, glatt, beständig gegen Wasser und Feuerlöschschaum.
Einlagen	Synthetische Textileinlagen.
Decke	Schwarzes EPDM Gummi, abrieb- und witterungsbeständig. Stoffgemustert.
Betriebsdruck	55 bar
Soll-Platzdruck	180 bar
Temperatur	-30° C + 80°C
Markierung	 THOR BS3169/1986 A2- size mm / 55 Bar (geprägt)

Technical Characteristics

Tube	Black smooth SBR/NR rubber, resistant to water and extinguishing foam.
Reinforcement	High tensile textile plies.
Cover	Black SBR/NR rubber, resistant to abrasion and weather conditions. Fabric impression.
Working Pressure	55 bar
Nominal Burst Pressure	180 bar
Temperature	-30°C +80°C
Marking	 THOR BS3169/1986 A2- size mm / 55 Bar (embossed)

Abmessungen / Sizes

Innendurchmesser Inner Diameter	Wanddicke Wall Thickness	Außendurchmesser Outside Diameter	Gewicht Weight	Biegeradius Bendino Radius
mm	mm	mm	Kg/m	mm
19	6,5	32	0,59	100
25	6	37	0,73	100